









FR 50T is designed for short distance wash. It is a super compact easy to set up LED Fresnel powered by 50 watts 2700K-6500K tunable white LED. Featuring 25° to 90° zoom, 95 CRI, 90 R9, rotary control of dimmer. It delivers a smooth, soft and flat field of light. A barn door is included to shape the light.

SOURCE Light source: 50 watts Tunable white COB LED

Color temperature: 2700K-6500K tunable

LED life expectancy: 50,000 Hrs.

CRI: 95; R9≥90

TLCI: 98

OPTICAL Manual zoom

SYSTEM Zoom range: 25° to 90° manual

Light output: 6600 Lux @ 1m @ 25°

KEY 5 Dimmer curves

FEATURES Strobe

Video flicker free

PMMA polymethyl methacrylate lens

Barn doors included

CONTROL & Control protocols: Rotary, DMX, RDM **PROGRAMMING** Control channels: 1, 2, 3, 4 CHs

ELECTRICAL Input voltage: AC100-240V/50-60Hz

CONNECTIONS DMX Connections: 3 pin XLR In/Out male and female

Power connections: PowerCon In/Out

PHYSICAL Dimensions: 230 x 156 x 279mm

Net weight: 1.7 Kg (barn door included)


Color: Black


Housing: Aluminum

IP rating: 20

Operating temperature: -5°C/45°C







Luminous Diagram

