



FLASH 88 is the complete IP65 LED wash light powered by 44 x 20 watts RGBW LEDs. In addition to its default long throw beam angle of 20°, it comes packed with a magnetic diffuser filter providing a wide 40° wash for medium throw applications. The ENTERTAINMENT powerful light output can also be shaped using the 4-way barn doors included with this fixture. Flash 88 features RDM control and is equipped with a built-in W-DMX™ wireless DMX receiver by Wireless Solution Sweden. SOURCE Light source: 44 x 20 watts, RGBW LEDs Dimensions LED life expectancy: 50,000 Hrs. 575 CRI < 80 **OPTICAL** Beam angle: 20° SYSTEM 40° with a magnetic diffuser filter Light output: 85,000 Lux @ 2m @ 30° Ö **DYNAMIC** Dimmer: 4 selectable dimming curves EFFECTS Color mixing: RGBW Strobe effect 210 Built-in color and dynamic macros CONTROL & Control protocols: DMX, RDM, W-DMX[™] by **PROGRAMMING** Wireless Solution 334 Display: OLED graphical display with 4 buttons Control channels: 2, 3, 4, 9 & 12 CHs ÎΗ ELECTRICAL Input voltage: 190-264V/50-60Hz Power consumption: 880 watts **Luminous Diagram** Power supply: Auto-ranging electronic switch-mode CONNECTIONS DMX connections: 3 pin XLR In/Out male and female 85,000 Lux Power connections: IP Powercon In/Out (m) 4 PHYSICAL Dimensions: 575 x 210 x 334mm 2 Net weight: 15.7 Kg 0 30° Color: Black Housing: Die-cast Aluminum 2 IP rating: 65 Operating temperature: -40°C/50°C Distance (m)