



SPARKLY LED 600P is a 600 watts LED moving head profile. It features four 180° rotatable shutter blades, iris and a zoom range from 6 to 42 degrees offering a full control on the light beam and coverage. It also has static and rotatable gobo wheels and a rotatable prism for a wide variety of effects. The output color is finely tuned with a CMY color mixing system and a CTO filter (2800-5600K) making it ideal for temporary and permanent theatrical, studio and stage applications.

SOURCE	Light source: 600 watts white LED LED life expectancy: 20000 Hrs. CRI > 75 (High CRI > 90 SKU: SparklyLED600PH)
OPTICAL SYSTEM	Beam angle: 6° to 42° Four shutter blades, 180° rotatable Electronic focus Iris
DYNAMIC EFFECTS	Dimmer: 0-100% linear adjustment Color mixing: CMY Color wheel: 7 colors + white CTO filter, 3200K to 6000K Static gobo: 8 gobos + open Rotating gobo: 6 gobos + open Prism: 4 facet prism Frost
CONTROL & PROGRAMMING	Control protocols: DMX, Master-Slave, Auto Run ECO Mode Display: 2.8" color LCD display, reversible 180° Control channels: 16, 24 CHs
MOVEMENT	Pan: 540° Tilt: 270° Resolution: 16 bit
ELECTRICAL	Input voltage: 110-240V/50-60Hz Power consumption: 700 watts
CONNECTIONS	DMX connections: 3 pin/5 pin XLR In/Out male and female Power connections: Powercon In
PHYSICAL	Dimensions: 404 x 306 x 736 mm Net weight: 32 Kg Color: Black IP rating: 20